

# Safety Data Sheet



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

**Product name** CRUMB RUBBER SPRAY  
**Synonyms** BITUMEN RUBBER SPRAY BINDER • S15RF • S18RF

### 1.2 Uses and uses advised against

**Uses** ROAD SURFACING

### 1.3 Details of the supplier of the product

**Supplier name** BORAL AUSTRALIA  
**Address** Triniti T2, Level 3, 39 Delhi Road, North Ryde, NSW, 2113, AUSTRALIA  
**Telephone** (02) 9220 6300  
**Website** <http://www.boral.com.au>

### 1.4 Emergency telephone numbers

**Emergency** 13 11 26 (Poisons Information Centre)

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### Physical Hazards

Flammable Liquids: Category 4

#### Health Hazards

Skin Corrosion/Irritation: Category 3

#### Environmental Hazards

Not classified as an Environmental Hazard

### 2.2 GHS Label elements

**Signal word** WARNING

#### Pictograms

#### Hazard statements

H227 Combustible liquid.  
H316 Causes mild skin irritation.

#### Prevention statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P262 Do not get in eyes, on skin, or on clothing.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

#### Response statements

P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P370 + P378 In case of fire: Use appropriate media to extinguish.

#### Storage statements

P403 Store in a well-ventilated place.

#### Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

## PRODUCT NAME CRUMB RUBBER SPRAY

### 2.3 Other hazards

This material is applied at elevated temperatures (typically above 180°C) with a mechanical pressurised sprayer. Contact with hot material can result in burns. The cured, inert semi solid material is considered non hazardous.

Please see package labelling or manufacturer's literature for more detail on usage, handling, storage and disposal under different applications.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
RECYCLED RUBBER FROM VEHICLE TYRES	-	-	5 to 20%
KEROSENE	8008-20-6	232-366-4	2 to 8%
ASPHALT	8052-42-4	232-490-9	73.5 to 82.5%
ADHESION AGENT	-	-	0.5%

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

<b>Eye</b>	If contact with hot material occurs, flush gently with cold running water. Adhered material should only be removed under the medical direction. Seek immediate medical advice.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If contact with hot material occurs, drench area immediately with cold water, do not attempt to remove material adhered to the skin. Seek immediate medical attention.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.
<b>First aid facilities</b>	Eye wash facilities and safety shower are recommended.

### 4.2 Most important symptoms and effects, both acute and delayed

Avoid contact with hot material, as burns may result. Bitumens, occupational exposure to straight-run bitumens and their emissions during road paving, are classified as possibly carcinogenic to humans (IARC Group 2B).

### 4.3 Immediate medical attention and special treatment needed

Burns caused by bitumen require special medical treatment. Consultation with a burns specialist experienced in bitumen burns is advisable in the first instance.

Refer to the Australian Asphalt Pavement Association (AAPA) bitumen burns card for further information (<http://www.aapa.asn.au>).

Bitumen burns: If hot bitumen contacts the skin, flush immediately with water and make no attempt to remove it. Use wet, cold towels if face, neck, shoulder or back etc are burnt. Cool burn areas for 30 minutes and seek immediate medical attention. Where bitumen completely circles a limb, it may have a tourniquet effect and should be split longitudinally as it cools. If eye burns result flush with water for 15 minutes, pad and seek immediate medical attention.

## 5. FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray. Do not use water jets.

### 5.2 Special hazards arising from the substance or mixture

Combustible. May evolve toxic gases (carbon/ sulphur/ nitrogen oxides, hydrogen sulphide, hydrocarbons) when heated to decomposition.

### 5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

### 5.4 Hazchem code

2Y	
2	Fine Water Spray.
Y	Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Allow material to cool. Contact emergency services where appropriate.

### 6.2 Environmental precautions

Contain material and prevent product from entering drains and waterways. Collect and seal in properly labelled containers for disposal. If contamination of sewers or waterways has occurred, contact local emergency services.

### 6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas. Fuming may occur at spraying temperatures but may be reduced if handled at temperatures below 150°C.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well ventilated area removed from ignition sources, oxidising agents and foodstuffs. Keep storage vessels closed when not in use. Take precautionary measures against electrostatic discharges. Avoid concentration of flammable volatiles in the headspace are of storage tanks / trucks. Bulk storage containers must be grounded/earthed, vented, and should have vapour emission controls. At no stage should the container be heated if in a packaged form. This does not apply if stored in a bulk vessel with specially designed heating systems.

### 7.3 Specific end uses

Not applicable.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Bitumen fume	SWA [AUS]	--	5	--	--
Kerosene (ACGIH)	SWA [AUS]	--	200	--	--

#### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

#### Engineering controls

Avoid inhalation by working upwind where possible. Use in well ventilated areas. Maintain vapour /fume levels below the recommended exposure standard.

## PRODUCT NAME CRUMB RUBBER SPRAY

### PPE

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

<b>Eye / Face</b>	Wear splash-proof goggles when handling hot material. Wear safety glasses when handling cold material.
<b>Hands</b>	Wear heat resistant leather or insulated gloves when handling hot material. Wear chemical resistant gloves (ie. Nitrile) when handling cold material.
<b>Body</b>	Avoid contact with skin and clothing. Wear impervious coveralls and heat resistant boots when handling hot material. When the risk of skin exposure is high, and impervious chemical suit may be required.
<b>Respiratory</b>	Where an inhalation risk exists in enclosed or partly enclosed environments (ie. underground car parks, large tanks, tunnels etc), wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator, dependent on a site specific risk assessment.



---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	HOT BLACK LIQUID (IN USE); BLACK SEMI SOLID THERMOPLASTIC MATERIAL (WHEN CURED)
<b>Odour</b>	BITUMEN-LIKE ODOUR
<b>Flammability</b>	CLASS C1 COMBUSTIBLE
<b>Flash point</b>	> 60.5°C
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Vapour density</b>	NOT AVAILABLE
<b>Relative density</b>	NOT AVAILABLE
<b>Solubility (water)</b>	INSOLUBLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT AVAILABLE
<b>Lower explosion limit</b>	NOT AVAILABLE
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	> 300°C
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT EXPLOSIVE
<b>Oxidising properties</b>	NON OXIDISING
<b>Odour threshold</b>	NOT AVAILABLE

### 9.2 Other information

<b>Avg weight/m<sup>2</sup> when cured</b>	1 kg/m <sup>2</sup>
<b>Expected temp. when cured</b>	Between ambient temperature and 20°C above ambient temperature
<b>Max temp. in use</b>	200°C

---

## 10. STABILITY AND REACTIVITY

---

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites) and acids (e.g. nitric acid). Do not allow hot material to contact liquids or water.

**10.6 Hazardous decomposition products**

May evolve toxic gases (carbon/ sulphur/ nitrogen oxides, hydrogen sulphide, hydrocarbons) when heated to decomposition.

**11. TOXICOLOGICAL INFORMATION****11.1 Information on toxicological effects**

**Acute toxicity** No known toxicity data is available for this product. Based on available data, the classification criteria are not met. Inhalation may cause headache, nausea and respiratory tract irritation. Once cured, the inert solid material is considered non hazardous.

**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
KEROSENE	> 2000 mg/kg (rat)	> 2000 mg/kg (rabbit)	> 5.28 mg/L/4hrs (rat)

**Skin** Contact with hot material may cause skin burns. Exposure to asphalt fumes may cause dermatitis and photosensitisation. Once cured, the inert semi solid material is considered non hazardous.

**Eye** Contact with hot material may cause eye burns. Exposure to asphalt fumes may cause irritation, redness or pain. Once cured, the inert semi solid material is unlikely to penetrate the eye and considered non hazardous.

**Sensitisation** Not classified as causing skin or respiratory sensitisation.

**Mutagenicity** Insufficient data available to classify as a mutagen.

**Carcinogenicity** Bitumens, occupational exposure to straight-run bitumens and their emissions during road paving, are classified as possibly carcinogenic to humans (IARC Group 2B).

**Reproductive** Insufficient data available to classify as a reproductive toxin.

**STOT - single exposure** Not classified as causing organ damage from single exposure. However, inhalation of bitumen fumes may cause headache, nausea and respiratory tract irritation. This material may release trace quantities of hydrogen sulphide within storage facilities.

**STOT - repeated exposure** Not classified as causing organ damage from repeated exposure.

**Aspiration** Not expected to present an aspiration hazard.

**12. ECOLOGICAL INFORMATION****12.1 Toxicity**

The bulk of the bitumen dispersed in asphalt is fairly inert when set, and should not present an environmental hazard under normal conditions.

**12.2 Persistence and degradability**

This product is not readily biodegradable.

**12.3 Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

**12.4 Mobility in soil**

Spillages are unlikely to penetrate the soil.

**12.5 Other adverse effects**

Avoid contamination of drains and waterways.

**13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

**Waste disposal** For small amounts dispose of to an approved landfill site. Contact the manufacturer for additional information if larger amounts are involved. Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

**Legislation** Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	3256	3256	3256
<b>14.2 Proper Shipping Name</b>	ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. WITH FLASH POINT ABOVE 60.5°C, AT or ABOVE ITS FLASH POINT	ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. WITH FLASH POINT ABOVE 60.5°C, AT or ABOVE ITS FLASH POINT	ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. WITH FLASH POINT ABOVE 60.5°C, AT or ABOVE ITS FLASH POINT
<b>14.3 Transport hazard class</b>	3	3	3
<b>14.4 Packing Group</b>	III	III	III

### 14.5 Environmental hazards

No information provided.

### 14.6 Special precautions for user

**Hazchem code** 2Y

**EmS** F-E, S-D

**Other information** This product is not considered a Dangerous Good when samples are transported at ambient temperatures.

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings** **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**  
All components are listed on AIIC, or are exempt.

## 16. OTHER INFORMATION

**Additional information** **PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**  
The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**  
It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**PRODUCT NAME CRUMB RUBBER SPRAY****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**