## **FINAL REPORT**

CERTIFICATE No.: 26081



Boral Cement Limited
ABN 62 008 528 523
Taylor Avenue New Berrima NSW 2577
Locked Bag 4 New Berrima NSW 2577
T +61 2 4860 2222

**TEST CERTIFICATE OF:** Geelong Daily Despatch General Purpose Bulk Cement

PRODUCED AT: Boral Cement Limited Geelong

**TESTED AT:** Berrima Works Laboratory

**SAMPLE IDENTIFICATION:** GDDGP2402370

DATE DESPATCHED: 5/28/2024

PROPERTY		REQUIREM	ENTS OF AS 3972		RESULT
Compressive Strength (A	AS/NZS 2350.11)				
3 Day	,				39.8 MPa
7 Day		Minimum	35 MPa		51.7 MPa
28 Day		Minimum	45 MPa		65.9 MPa
Setting Time (AS/NZS 2	2350.4)				
Initial		Minimum	45 mins		120 mins
Final		Maximum	360 mins		165 mins
Soundness (AS/NZS 2350.5)		Maximum	5 mm		1 mm
SO <sub>3</sub> (AS 2350.2)		Maximum	3.5 %		3.0 %
CI (AS 2350.2)		Maximum	0.10 %		0.02 %
OTHER REPORTABLE	PROPERTIES				
CHEMICAL			PHYSICAL		
K <sub>2</sub> O (AS 2350.2)	0.38 %		Normal Consistency	(AS/NZS 2350.3)	28.0 %
Na <sub>2</sub> O (AS 2350.2)	0.25 %		Fineness Index	(AS/NZS 2350.8)	385 m <sup>2</sup> /kg
LOI (AS 2350.2)	2.1 %				·

## **REMARKS**

Preparation of mortar and moulding of specimens in accordance with AS 2350.12.

Sampling not carried out by laboratory. Samples tested as received and results only relate to the item tested.

This cement is a Type GP cement with up to 7.5% mineral addition.

Shaller

Accredited for compliance with ISO/IEC 17025 - Testing

NATA Accreditation Number: 530 / 531

Page 1 of 1

Jason Nairn (National Technical Manager)

Date of Issue: 7/11/2024