## **FINAL REPORT**

CERTIFICATE No.: 24343



Boral Cement Limited N 62 008 528 523 Taylor Avenue New Berrima NSW 2577 Locked Bag 4 New Berrima NSW 2577 T +61 2 4860 2222

| TEST CERTIFICATE OF:   | Maldon Daily Despatch Off White Bagged Cement |  |  |  |
|------------------------|---|--|--|--|
| PRODUCED AT:           | Boral Cement Limited Maldon                   |  |  |  |
| TESTED AT:             | Berrima Works Laboratory                      |  |  |  |
| SAMPLE IDENTIFICATION: | MBGOW2204336                                  |  |  |  |
| DATE DESPATCHED:       | 30/11/2022                                    |  |  |  |

| PROPERTY                          | REQUIREME | ENTS OF AS 3972 | RESULT   |
|-----------------------------------|-----------|-----------------|----------|
| Compressive Strength (AS 2350.11) |           |                 |          |
| 3 Day                             |           |                 | 37.1 MPa |
| 7 Day                             | Minimum   | 35 MPa          | 50.0 MPa |
| 28 Day                            | Minimum   | 45 MPa          | 63.9 MPa |
| Setting Time (AS 2350.4)          |           |                 |          |
| Initial                           | Minimum   | 45 mins         | 135 mins |
| Final                             | Maximum   | 360 mins        | 195 mins |
| Soundness (AS 2350.5)             | Maximum   | 5 mm            | 1 mm     |
| SO <sub>3</sub> (AS 2350.2)       | Maximum   | 3.5 %           | 2.7 %    |
| CI (AS 2350.2)                    | Maximum   | 0.10 %          | 0.01 %   |

| OTHER REPORTABLE PROPERTIES |            |        |                    |               |           |  |  |
|-----------------------------|------------|--------|--------------------|---------------|-----------|--|--|
| CHEMIC                      | AL         |        | PHYSICAL           |               |           |  |  |
| K <sub>2</sub> O (A         | NS 2350.2) | 0.41 % | Normal Consistency | (AS 2350.3)   | 27.3 %    |  |  |
| Na <sub>2</sub> O (A        | NS 2350.2) | 0.05 % | Fineness Index     | (AS 2350.8)   | 365 m²/kg |  |  |
| LOI (A                      | S 2350.2)  | 4.1 %  | Brightness *       | (TM 10.01.12) | 70.5 %    |  |  |
|                             |            |        |                    |               |           |  |  |

## REMARKS

Preparation of mortar and moulding of specimens in accordance with AS 2350.12.

Sampling not carried out by laboratory. Samples tested as received.

This cement is a Type GP cement with up to 7.5% mineral addition.

\* NATA accreditation does not cover the performance of this service.



Marc Smith Technical Services Manager