







UltraPatch

READY-TO-USE ASPHALT

UltraPatch is the only Australian product using Macfix® technology. This internationally recognised formula provides the unique benefits of UltraPatch.



Long-term solution

- Suitable for use under spray-sealed and paved surfaces
- Store for up to two years

Suitable for roads and footpaths

• Surface can be trafficked immediately

Easy to handle and apply

- Ready-to-use mixture
- Can be applied in all weather conditions
- Non-toxic formula
- No tack coat necessary

Made in Australia

- Manufactured and tested under stringent quality controlled conditions
- Certified as Australian Made®

Various sizes available

Available in 15kg bags, 20kg pails, one-tonne bulk bags and loose bulk

SUITABLE FOR:





Patches



Trenches



Core reinstatements



Roads



Footpaths



Residential




al Concrete & s Asphalt




INSTRUCTIONS FOR USE



 Clear pothole of loose debris and excess water to give clean solid supporting edges.



2. Add a 25mm to 50mm layer of UltraPatch.



Compact thin layers with a hand tamper or use a plate compactor for heavy trafficked areas.



4. Repeat steps 2 and 3 until the repair is at the required level.



5. Surface can be used immediately after placement.

Quick tips:

- The optimum thickness of UltraPatch is 50mm.
- If using UltraPatch for a road repair, ensure compacted product is 10mm above surrounding surface.
- If minor settlement occurs over time due to soft base materials, add UltraPatch to return to the required level.
- It is best to lightly dust the surface with sand if repair is to be trafficked immediately by turning vehicles.
- Contact Boral for advice prior to applying UltraPatch in works with dimensions greater than 2 metres in length or breadth, or repairs deeper than 150mm.

Coverage

| Thickness of compacted asphalt repair | | | | |
|---|-------|-------|------|------|
| One tonne of UltraPatch will cover the following area. | 25mm | 40mm | 50mm | 75mm |
| Area (m²) | 16-18 | 11-13 | 8-9 | 5-6 |





Watch our video showing the instructions for use by scanning the QR code with your phone camera or visit www.boral.com.au/ultrapatch

UltraPatch is available in a range of convenient sizes:



SAFETY

UltraPatch is handled and applied at ambient temperatures so there is no risk of skin burns. Unlike most cold mix asphalt, Boral UltraPatch does not contain toxic solvents which can be harmful to workers and the environment.

Please wear gloves and ensure adequate ventilation when handling and placing UltraPatch.

A safety data sheet is available at www.boral.com.au/asphalt

STORAGE

UltraPatch should be kept in original packaging and out of reach of children. UltraPatch can be stored for up to two years.

During storage a crust may harden on the surface. To restore workability, tip UltraPatch onto a clean surface and manipulate.

CONTACT US

Visit www.boral.com.au/asphalt for more information about Boral's range of asphalt products.

For orders and enquiries about UltraPatch, please call us on

1800 555 445

or email ultrapatch@boral.com.au

The particular circumstances of asphalt projects, including site conditions, equipment and weather can vary significantly and dictate the use of particular materials and techniques to address challenges presented by those circumstances. The application guide should be viewed as a general reference only. Boral recommends you seek professional advice tailored to your project before using this product.

BORAL

©2020 Boral Limited. Boral, the Boral logo and Build something great are trade marks or registered trade marks of Boral Limited or one of its subsidiaries. Copyright Boral Construction Materials Limited ACN 000 614 826 – all rights reserved 2020. BCC_17473 02/2022