FINAL REPORT

CERTIFICATE No.: 23428



Boral Cement Limited ABN 62 008 528 523 Taylor Avenue New Berrima NSW 2577 Locked Bag 4 New Berrima NSW 2577

> T +61 2 4860 2222 F +61 2 4860 2257

TEST CERTIFICATE OF: Berrima Daily Despatch High Early Strength Cement

PRODUCED AT: Boral Cement Limited Berrima

TESTED AT: Berrima Works Laboratory

SAMPLE IDENTIFICATION: BWDHE2200791 **DATE DESPATCHED:** 21/03/2022

| PROPERTY | | REQUIREMENTS OF AS 3972 | | | RESULT |
|-------------------------------|-------------|-------------------------|--------------------|-------------|------------------------|
| Compressive Strength (| AS 2350.11) | | | | |
| 3 Day | • | Minimum | 25 MPa | | 42.9 MPa |
| 7 Day | | Minimum | 40 MPa | | 53.3 MPa |
| 28 Day | | | | | 63.4 MPa |
| Setting Time (AS 2350. | 4) | | | | |
| Initial | | Minimum | 45 mins | | 90 mins |
| Final | | Maximum | 360 mins | | 150 mins |
| Soundness (AS 2350.5) | | Maximum | 5 mm | | 1 mm |
| SO ₃ (AS 2350.2) | | Maximum | 3.5 % | | 2.7 % |
| CI (AS 2350.2) | | Maximum | 0.10 % | | 0.01 % |
| OTHER REPORTABLE | PROPERTIES | | | | |
| CHEMICAL | | | PHYSICAL | | |
| K ₂ O (AS 2350.2) | 0.62 % | | Normal Consistency | (AS 2350.3) | 29.7 % |
| Na ₂ O (AS 2350.2) | 0.05 % | | Fineness Index | (AS 2350.8) | 460 m ² /kg |
| LOI (AS 2350.2) | 1.2 % | | | | · |

REMARKS

Preparation of mortar and moulding of specimens in accordance with AS 2350.12.

Sampling not carried out by laboratory. Samples tested as received.

This cement is a Type HE (GP) cement.

Jul.

Marc Smith
Technical Services Manager
Date of Issue: 18/05/2022

Accredited for compliance with ISO/IEC 17025 - Testing

NATA Accreditation Number: 530 / 531

Page 1 of 1