FINAL REPORT

CERTIFICATE No.: 23840



Boral Cement Limited N 62 008 528 523 Taylor Avenue New Berrima NSW 2577 Locked Bag 4 New Berrima NSW 2577 T +61 2 4860 2222

| TEST CERTIFICATE OF: | Berrima Daily Despatch High Early Strength Cement |
|------------------------|---|
| PRODUCED AT: | Boral Cement Limited Berrima |
| TESTED AT: | Berrima Works Laboratory |
| SAMPLE IDENTIFICATION: | BWDHE2202199 |
| DATE DESPATCHED: | 4/07/2022 |

| REQUIREM | ENTS OF AS 3972 | RESULT |
|----------|--|---|
| | | |
| Minimum | 25 MPa | 41.8 MPa |
| Minimum | 40 MPa | 54.6 MPa |
| | | 65.0 MPa |
| | | |
| Minimum | 45 mins | 105 mins |
| Maximum | 360 mins | 135 mins |
| Maximum | 5 mm | 1 mm |
| Maximum | 3.5 % | 2.7 % |
| Maximum | 0.10 % | 0.01 % |
| | Minimum Minimum Maximum Maximum Maximum Maximum | Minimum40 MPaMinimum45 minsMaximum360 minsMaximum5 mmMaximum3.5 % |

| OTHER REPORTABLE PROPERTIES | | | | | | |
|-----------------------------|-------------|--------|--------------------|-------------|------------------------|--|
| CHEMICAL | | | PHYSICAL | | | |
| K ₂ O | (AS 2350.2) | 0.56 % | Normal Consistency | (AS 2350.3) | 29.8 % | |
| Na ₂ O | (AS 2350.2) | 0.11 % | Fineness Index | (AS 2350.8) | 450 m ² /kg | |
| LOI | (AS 2350.2) | 1.2 % | | | | |
| | | | | | | |

REMARKS

Preparation of mortar and moulding of specimens in accordance with AS 2350.12. Sampling not carried out by laboratory. Samples tested as received. This cement is a Type HE (GP) cement.

Marc Smith Technical Services Manager Date of Issue: 2/09/2022

