## **FINAL REPORT**

CERTIFICATE No.: 24751



Boral Cement Limited N 62 008 528 523 Taylor Avenue New Berrima NSW 2577 Locked Bag 4 New Berrima NSW 2577 T +61 2 4860 2222

TEST CERTIFICATE OF: Berrima Daily Despatch High Early Strength Cement

PRODUCED AT: Boral Cement Limited Berrima

**TESTED AT:** Berrima Works Laboratory

SAMPLE IDENTIFICATION: BWDHE2301246

DATE DESPATCHED: 11/04/2023

| ROPERTY                       |             | REQUIREME | REQUIREMENTS OF AS 3972 |             | RESULT                 |
|-------------------------------|-------------|-----------|-------------------------|-------------|------------------------|
| Compressive Strength (        | AS 2350.11) |           |                         |             |                        |
| 3 Day                         | •           | Minimum   | 25 MPa                  |             | 41.4 MPa               |
| 7 Day                         |             | Minimum   | 40 MPa                  |             | 51.5 MPa               |
| 28 Day                        |             |           |                         |             | 62.3 MPa               |
| Setting Time (AS 2350.        | 4)          |           |                         |             |                        |
| Initial                       |             | Minimum   | 45 mins                 |             | 120 mins               |
| Final                         |             | Maximum   | 360 mins                |             | 165 mins               |
| Soundness (AS 2350.5          | )           | Maximum   | 5 mm                    |             | 1 mm                   |
| SO <sub>3</sub> (AS 2350.2)   |             | Maximum   | 3.5 %                   |             | 2.8 %                  |
| CI (AS 2350.2)                |             | Maximum   | 0.10 %                  |             | 0.02 %                 |
| OTHER REPORTABLE              | PROPERTIES  |           |                         |             |                        |
| CHEMICAL                      |             |           | PHYSICAL                |             |                        |
| K <sub>2</sub> O (AS 2350.2)  | 0.50 %      |           | Normal Consistency      | (AS 2350.3) | 29.7 %                 |
| Na <sub>2</sub> O (AS 2350.2) | 0.08 %      |           | Fineness Index          | (AS 2350.8) | 450 m <sup>2</sup> /kg |
| LOI (AS 2350.2)               | 1.4 %       |           |                         | •           | ·                      |

## **REMARKS**

Preparation of mortar and moulding of specimens in accordance with AS 2350.12.

Sampling not carried out by laboratory. Samples tested as received.

This cement is a Type HE (GP) cement.

Jul.

Marc Smith
Technical Services Manager
Date of Issue: 17/05/2023

Accredited for compliance with ISO/IEC 17025 - Testing

NATA Accreditation Number: 530 / 531

Page 1 of 1