FINAL REPORT

CERTIFICATE No.: 23204



Boral Cement Limited ABN 62 008 528 523 Taylor Avenue New Berrima NSW 2577 Locked Bag 4 New Berrima NSW 2577

> T +61 2 4860 2222 F +61 2 4860 2257

TEST CERTIFICATE OF: Maldon Daily Despatch General Purpose Bagged Cement

PRODUCED AT: Boral Cement Limited Maldon
TESTED AT: Berrima Works Laboratory

SAMPLE IDENTIFICATION: MBGGP2200095
DATE DESPATCHED: 11/01/2022

PROPERTY	REQUIREMENTS OF AS 3972	RESULT
SO ₃ (AS 2350.2) CI (AS 2350.2)	Maximum 3.5 % Maximum 0.10 %	2.6 % 0.03 %

OTHER REPORTABLE PROPERTIES CHEMICAL K₂O (AS 2350.2) 0.48 % Fineness Index (AS 2350.8) 415 m²/kg Na₂O (AS 2350.2) 4.0 %

REMARKS

Sampling not carried out by laboratory. Samples tested as received. This cement is a Type GP cement with up to 7.5% mineral addition.

Marc Smith
Technical Services Manager

Date of Issue: 29/03/2022



Boral Construction Materials Materials Technical Services

Unit 4, 3-5 Gibbon Road Baulkham Hills NSW 2153 Australia

PO Box 400, Winston Hills NSW 2153

T +61 (02) 9624 9900

TEST REPORT

boral.com.au

CLIENT:

BORAL CEMENT - (TECHNICAL)

FILE NO: 50/22

ADDRESS:

39 Delhi Road, North Ryde, NSW 2113

REQUEST NO:

98668

TEST METHOD: AS/NZS 2350: Method of Testing Portland and Blended Cements

CEMENT IDENTIFICATION: MBGGP2200095 LAB. SAMPLE NO:

264965

SAMPLE SOURCE:

Maldon

DATE SAMPLED:

11/01/2022

DATE RECEIVED:

21/03/2022

Results

Date of cast: 28/03/2022

PROPERTY	DATE TESTED	TEST METHOD	RESULT
Compressive strength - 3 days Compressive strength - 7 days Compressive strength - 28 days Normal Consistency Setting Time Initial Set Final Set Soundness	31/03/2022	AS/NZS 2350.11	34.6 MPa
	04/04/2022	AS/NZS 2350.11	43.4 MPa
	25/04/2022	AS/NZS 2350.11	53.0 MPa
	29/04/2022	AS/NZS 2350.3	28.0%
	29/04/2022	AS/NZS 2350.4	165 Minutes
	29/04/2022	AS/NZS 2350.4	225 Minutes
	30/04/2022	AS/NZS 2350.5	1 mm

Note:

Cement was provided by the client and tested as received.

Marc Smith, Parisa Sowti, Violeta Paicu, Mat. File, File

Julius Alvaro Approved Sign CEM98668.JA.5 Serial No.



