## **FINAL REPORT**

**CERTIFICATE No.:** 24899



Boral Cement Limited N 62 008 528 523 Taylor Avenue New Berrima NSW 2577 Locked Bag 4 New Berrima NSW 2577 T +61 2 4860 2222

TEST CERTIFICATE OF: Maldon Daily Despatch Off White Cement

PRODUCED AT: Boral Cement Limited Maldon
TESTED AT: Berrima Works Laboratory

SAMPLE IDENTIFICATION: MDDOW2301815

**DATE DESPATCHED:** 22/05/2023

| PROPERTY                      | REQUIREMENTS OF AS 3972 |         |      |                    | RESULT        |                        |
|-------------------------------|-------------------------|---------|------|--------------------|---------------|------------------------|
| Compressive Strength (A       | AS 2350.11)             |         |      |                    |               |                        |
| 3 Day                         | ,                       |         |      |                    |               | 38.3 MPa               |
| 7 Day                         |                         | Minimum | 35   | MPa                |               | 50.7 MPa               |
| 28 Day                        |                         | Minimum | 45   | MPa                |               | 65.8 MPa               |
| Setting Time (AS 2350.        | 4)                      |         |      |                    |               |                        |
| Initial                       |                         | Minimum | 45   | mins               |               | 135 mins               |
| Final                         |                         | Maximum | 360  | mins               |               | 195 mins               |
| Soundness (AS 2350.5          | )                       | Maximum | 5    | mm                 |               | 1 mm                   |
| SO <sub>3</sub> (AS 2350.2)   |                         | Maximum | 3.5  | %                  |               | 2.8 %                  |
| CI (AS 2350.2)                |                         | Maximum | 0.10 | %                  |               | 0.02 %                 |
| OTHER REPORTABLE              | PROPERTIES              |         |      |                    |               |                        |
| CHEMICAL                      |                         |         |      | PHYSICAL           |               |                        |
| K <sub>2</sub> O (AS 2350.2)  | 0.43 %                  |         |      | Normal Consistency | (AS 2350.3)   | 27.2 %                 |
| Na <sub>2</sub> O (AS 2350.2) | 0.07 %                  |         |      | Fineness Index     | (AS 2350.8)   | 390 m <sup>2</sup> /kg |
| LOI (AS 2350.2)               | 3.7 %                   |         |      | Brightness *       | (TM 10.01.12) | 71.6 %                 |

## **REMARKS**

Preparation of mortar and moulding of specimens in accordance with AS 2350.12.

Sampling not carried out by laboratory. Samples tested as received.

This cement is a Type GP cement with up to 7.5% mineral addition.

\* NATA accreditation does not cover the performance of this service.

Jul.

Marc Smith
Technical Services Manager
Date of Issue: 28/07/2023