

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name	BLENDED CEMENT
Synonyms	BLUE CIRCLE BUILDERS CEMENT • BLUE CIRCLE SPECIAL PURPOSE CEMENT • BUILDERS CEMENT • FA BLEND • FLY ASH BLEND • GB CEMENT • GENERAL BLEND • GENERAL PURPOSE BLENDED CEMENT • GP SLAG BLEND • LOW HEAT CEMENT • MARINE CEMENT • POZZOMENT • SLAG BLEND • SLAGMENT • SPECIAL PURPOSE CEMENT • SULFATE RESISTING CEMENT • TRIPLE BLEND • TYPE GB • TYPE LH • TYPE SR

1.2 Uses and uses advised against

Uses	BINDER - REFRACTORIES • CONCRETE • CONSTRUCTION • GROUT • INDUSTRIAL APPLICATIONS • MANUFACTURE OF CEMENTS • MASONRY • MORTAR • SOIL STABILISATION
-------------	--

1.3 Details of the supplier of the product

Supplier name	BORAL AUSTRALIA
Address	Level 18, 15 Blue Street, North Sydney, NSW, 2060, AUSTRALIA
Telephone	(02) 9220 6300
Website	http://www.boral.com.au

1.4 Emergency telephone numbers

Emergency	1800 555 477 (8am – 5pm WST)
Emergency (A/H)	13 11 26 (Poisons Information Centre)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Not classified as a Physical Hazard

Health Hazards

Skin Corrosion/Irritation: Category 2
Serious Eye Damage / Eye Irritation: Category 1
Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)
Carcinogenicity: Category 1
Specific Target Organ Toxicity (Repeated Exposure): Category 2

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms



PRODUCT NAME BLENDED CEMENT**Hazard statements**

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H350i May cause cancer by inhalation.
 H373 May cause damage to organs through prolonged or repeated exposure.

Prevention statements

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.

Response statements

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P362 Take off contaminated clothing and wash before re-use.

Storage statements

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

Disposal statements

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content
PORTLAND CEMENT	65997-15-1	266-043-4	20 to 90%
LIMESTONE (CALCIUM CARBONATE)	1317-65-3	215-279-6	<7.5%
GYPSUM	13397-24-5	603-783-2	<5%
QUARTZ (CRYSTALLINE SILICA)	14808-60-7	238-878-4	<5%
CALCIUM OXIDE	1305-78-8	215-138-9	<3%
HEXAVALENT CHROMIUM	18540-29-9	-	<0.002%
SLAGS, FERROUS METAL, BLAST FURNACE	65996-69-2	266-002-0	<80%
ASHES (RESIDUES)	68131-74-8	268-627-4	<40%
MAGNESIUM OXIDE	1309-48-4	215-171-9	<3%

Ingredient Notes 1. Depending upon the source material, may contain varying amounts of respirable quartz (crystalline silica).
 2. Chromium VI is a trace impurity in Portland Cement (< 20 ppm).

4. FIRST AID MEASURES**4.1 Description of first aid measures**

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Chronic over exposure to silica quartz dust may result in silicosis (lung disease). Principal symptoms of silicosis are coughing and breathlessness. Some individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

4.3 Immediate medical attention and special treatment needed

Treat as for moderate to strong alkali and symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

5.3 Advice for firefighters

No fire or explosion hazard exists.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Calcium carbonate (Limestone, Marble, Whiting)	SWA [AUS]	--	10	--	--
Calcium oxide	SWA [AUS]	--	2	--	--
Calcium oxide	SWA [Proposed]	--	1	--	--
Chromium (VI) (as Cr)	SWA [Proposed]	--	7E-6	--	--
Chromium (VI) compounds (as Cr)	SWA [AUS]	--	0.05	--	--
Gypsum (Calcium sulphate)	SWA [AUS]	--	10	--	--
Magnesium oxide (fume)	SWA [AUS]	--	10	--	--
Portland Cement	SWA [AUS]	--	10	--	--
Quartz (respirable dust)	SWA [AUS]	--	0.1	--	--
Quartz (respirable dust)	SWA [Proposed]	--	0.05	--	--
Quartz (respirable dust)	WorkSafe VIC	--	0.05	--	--

PRODUCT NAME BLENDED CEMENT

Biological limits


No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

PPE

Eye / Face	Wear safety glasses or dust-proof goggles when handling material to avoid contact with eyes.
Hands	Wear PVC, rubber or cotton gloves when handling material to prevent skin contact.
Body	Wear long sleeved shirt and full-length trousers.
Respiratory	Where an inhalation risk exists wear a Class P1 (Particulate) respirator, dependent on a site specific risk assessment.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	FINE OFF-WHITE TO DARK GREY POWDER
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	> 1200°C
Evaporation rate	NOT AVAILABLE
pH	11 to 13
Vapour density	NOT AVAILABLE
Specific gravity	2.9 to 3.2
Solubility (water)	< 10 g/L
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

9.2 Other information

Density	1100 - 1550 kg/m ³ (Bulk)
----------------	--------------------------------------

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerisation is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

PRODUCT NAME BLENDED CEMENT

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity No known toxicity data is available for this product. Based on available data, the classification criteria are not met.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
LIMESTONE (CALCIUM CARBONATE)	> 5000 mg/kg (rat)	--	--

Skin Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and dermatitis.

Eye Causes serious eye damage. Contact with moisture in the eyes may result in irritation, lacrimation, pain, redness, conjunctivitis and possible alkaline burns aided by mechanical irritation and abrasion.

Sensitisation Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.

Mutagenicity Insufficient data available to classify as a mutagen.

Carcinogenicity This product contains crystalline silica which is classified as carcinogenic to humans (IARC Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis. Therefore, preventing the onset of silicosis will also reduce the cancer risk. Hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1), however due to the trace amounts present, the criteria for classification is not met.

Reproductive Insufficient data available to classify as a reproductive toxin.

STOT - single exposure Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in breathing difficulties.

STOT - repeated exposure Repeated exposure to respirable silica may result in pulmonary fibrosis (silicosis). Silicosis is a fibronodular lung disease caused by deposition in the lungs of fine respirable particles of crystalline silica. Principal symptoms of silicosis are coughing and breathlessness. In the wet state, the likelihood of an inhalation hazard is reduced.

Aspiration This product is a solid and aspiration hazards are not expected to occur.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

May be harmful to the aquatic environment due to the alkaline nature of the product. This product is non-toxic to aquatic organisms when present as a cured solid.

12.2 Persistence and degradability

Product is persistent and would have a low degradability.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate.

12.4 Mobility in soil

A low mobility would be expected in a landfill situation.

12.5 Other adverse effects

Avoid contamination of drains and waterways.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).

PRODUCT NAME **BLENDED CEMENT**

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.
Inventory listings	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PRODUCT NAME BLENDED CEMENT**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]