

Blackbutt 670 x 134 x 14mm

NEW Engineered Herringbone Parquetry™

Features and Benefits

- Coated with a 10% UV cured acrylic matte and brushed for added texture
- The 4mm nominal hardwood top layer allows re-sanding and re-coating for a long service life
- Each board is end matched and tongue and grooved for a tight board-to-board fit and consistent finish
- The clear coating highlights the natural colour and timber finishes
- No mess and fumes from sanding and finishing

Installation Requirements

Boral Engineered Herringbone™ Parquetry must be glued down over a level subfloor such as a concrete slab, particleboard or plywood sheeting or over old timber floors. For further information, see the Boral Engineered Herringbone Parquetry™ installation guide. It is recommended that parquetry flooring is installed by a professional as it requires specific methodology and equipment.

Specifications

Board Size	670 x 134 x 14mm
m² Per Board	0.089
Boards Per Box	12 (6 left and 6 right boards)
m² Per Box	1.077
Boxes Per Pallet	44
m² Per Pallet	47.403

Grade - Standard & Better

Carefully graded to include the most interesting and moderate features of Australiana grade flooring. This grade offers a minimum level of natural features best suited to a modern style.

Species

Blackbutt



Spotted Gum



Promoting sustainable forest management

16946_BCC 2/20

For more information, contact your Account Manager or call **1800 818 317** or visit **www.boral.com.au/timber**

Note: Variations of colour within a timber species are normal, therefore photographs, samples and displays can only be indicative of the colour range of the timber species nominated. Timber is a natural product and commonly reacts to changes in atmospheric and environmental conditions such as humidity and temperature. This is considered normal. It is recommended that species are viewed at a timber showroom before a decision is made on colour.